





|                               |   |
|-------------------------------|---|
| <b>General:</b>               | Assembled by A&I Manufacturing, Inc. <b>Environmentally safe.</b>   |
| <b>Head Rail:</b>             | 2" x 2" x 0.024" Steel. Treated to resist corrosion. Baked-on paint, color coordinated to slats.  |
| <b>Bottom Rail:</b>           | Trapezoid shape, made of composite materials. Color coordinated to match slats.   |
| <b>Slats:</b>                 | Foam composite, 2" wide x 0.125" thick.   |
| <b>Valance:</b>               | Composite Royal Valance. Standard outside mount returns 3".   |
| <b>Tilter:</b>                | Shall be of worm gear construction, enclosed in housing of engineered polymer. May be positioned at right or left with or without cord lock.  |
| <b>Tilt Rod:</b>              | Shall be solid steel with corrosion resistant finish.   |
| <b>Tilt Wands:</b>            | Shall be extruded, clear solid acrylic with tubular construction.   |
| <b>Cordless Modules:</b>      | Cordless modules are constructed with opaque PVC body. Lift cord is wound inside the module. Steel spring provides tension to pull the shade up.  |
| <b>Cord lock:</b>             | Shall be of Snap-In-Design and incorporates stainless steel wear guard over which cords pass and a floating type locking pin. Locking pin shall be free of abrasive teeth and offer minimum wear to the cord. |
| <b>Lift Cords:</b>            | Shall be two-ply polyester cord filler and braided polyester jacket.  |
| <b>Braided Ladders:</b>       | Shall be 100% polyester yarn color coordinated with the slats. Spacing shall not be more than 44mm (approximately 7 slats per foot of drop).  |
| <b>Installation Brackets:</b> | End brackets shall be 2" x 2" .042" steel box brackets. Blinds over 48" shall have intermediate supports.   |
| <b>Tassel:</b>                | Shall comply with all safety requirements   |
| <b>Sizes:</b>                 | Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal blinds will have 1/2" deducted at the factory from width. See Product Limits.                          |

**Product Limits**

| Controls (Manual)           | Min. Width | Max. Width | Min. Drop | Max. Drop |
|-----------------------------|------------|------------|-----------|-----------|
| Split Controls-[L/R or R/L] | 12"        | 84"        | 10"       | 84"       |

|  |  |  |
|--|--|--|
|  <p><b>WARNING</b><br/><b>ADVERTENCIA</b></p> |  | <p>Window Blind Cord Can STRANGLE Your Child.<br/>Keep cords out of children's reach. Shorten cords to prevent reach.<br/>Move crib and furniture away – Children can climb furniture to reach cords.</p>  |
|  |  | <p>La cuerda de la persiana puede ESTRANGULAR a su niño.<br/>Mantenga las cuerdas fuera del alcance de los niños. Acorte las cuerdas para evitar el al.<br/>Mueva la cuna y los muebles – Los niños pueden subir los muebles para alcanzar las o</p> |

